

Torque values of fasteners:

1. Rear Fork Pivot Shaft Nut 40 – 45 ft/lbs
2. 7/16 – 14 x 1 ½ hex head cap screw 38 – 42 ft/lbs
3. 3/8–16 x 1 button head cap screw for the upper mount
12 ft/lbs
4. 3/8–16 nyloc nut on the rear suspension studs 12 ft/lbs
5. ½ - 13 x 2 hex head cap screw 75 ft/lbs
6. 7/16 – 20 x 1 ½ hex head cap screw 38 – 42 ft/lbs

Maintenance Schedule:

Item \ Frequency	Daily	4,000	6,000	8,000	12,000	16,000	20,000	24,000
Belts	I	I	I	I	I	I	I	I
A-arm grease Zerk fittings							L	
Brake Pads and Rotors [1]		I		I	I	I	I	I
Half Shaft Boots		I		I	I	I	I	I
Belt Tension		I		I		I		I
Wheel Bearings		I		I	I	I	I	I
Wheels and Tires		I		I	I	I	I	I
All Lighting	I							
Tire Pressure	I							
Brake fluid		I		I	R	I	I	R

I: Inspect and clean, adjust, lubricate, and/or replace if necessary.

R: Replace

L: Lubricate

NOTE:

[1] Minimum pad thickness is .04 inches (1.02mm)

At higher odometer readings, repeat at frequency intervals established here.